



Surge Protective Device

MPM8-AV
Plug-In Surge Protector

Technical Documentation



The MPM8-AV Multimedia Power Strip suppressor has eight receptacles to power your sensitive electronics. Its high energy circuitry absorbs and reroutes surge energy to ground or in the event of catastrophic surge, completely disconnects power.

The MPM8-AV receptacles are spaced to fit power blocks (transformers). Diagnostic lights indicate proper grounding and outlet wiring.

Key Specs

- **IMPROVES PICTURE AND SOUND QUALITY**
- **SURGE PROTECTION**

Features

- 8 protected power receptacles
- Twin video suppressors
- Telephone suppressor
- Includes video/phone cables
- Nanosecond Speed
- Meets IEEE587CAT.B
- Multi-Functional indicators

General Technical Specifications

Weight	3.5 lbs.
Voltage Protection Rating	500V
Thermal Fusing	Yes
Single Pulse Energy Dissipation	1125 Joules
Response Time	< 1ns
Protection Modes	L-N, L-G, N-G
Peak Impulse Current	52,000 A
Maximum Current Rating	15A(1800W)
Line Voltage	120VAC, 50/60Hz
Initial Clamping Level	200V Peak, 141V RMS
EMI/RFI Noise Filtration	45 dB(100 KHz - 1MHz)

Ordering Information

MODEL

MPM8-AV

KENICK
11400 47th St N Ste A
Clearwater, FL 33762
Phone: (800) 362-9997
www.KENICK.com



While every precaution has been taken to ensure accuracy and completeness herein, Kenick assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.

Rev0 05-20