



The PJ40 provides the benefits of advanced surge suppression technology in an ultra-slim form factor. Simple wall mounting, and easy access receptacles make PJ40 ideal for mounting behind thin display screens as used in hotels, restaurants, hospitals, campuses, airports and other commercial areas.

While the PJ40's compact design is appealing to the digital signage industry, it is also excellent for providing protection to kiosks, gaming machines, computers, point-of-sale equipment, and small printers.

Key Specs

- **Light Weight:** 2.0 lbs
- **Slim:** 1.22"

Features

- Input cord, optional detachable offset, right angle 5–15P power cord provides flexible installation
- Flat installation, power inlet, receptacles, and RJ45 connections are located on the unit sides
- Power reset, includes a reset button to allow manual cycling of power

General Technical Specifications

Input Capacity	10A
Input Voltage	120 VAC
Input Frequency	50/60HZ
Output Voltage	120VAC
Output Frequency	50/60Hz
Output Surge Suppression	2400 joules
Dimensions (W x D x H)	8.07x3.35x1.22in
Weight	2.0lbs
Line cord	Optional C13 to 5-15P
Receptacles	(3) 5-15R
Remote power control	Available in other model versions
Environment Temperature	-4–158°F (-20–70°C)
Environment Humidity	0-90%
Environment Altitude	11,500 FT ABOVE SEA LEVEL
Warranty	3 year warranty

Front and Back

DIAGRAM 1



DIAGRAM 2



KENICK
11400 47th St N Ste A
Clearwater, FL 33762
Phone: (800) 362-9997
www.KENICK.com



While every precaution has been taken to ensure accuracy and completeness herein, Kenick assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.

Rev0 05-20